



*Ideal For Replacement & New Construction*  
**Premium Vinyl Doors • Series 9900 & 9901**  
**Sliding Doors**

**The Best Is Always Superior™**

*Product Information Sheet*


Series 9900 and 9901 Premium Vinyl Sliding Doors are manufactured in California by Superior Windows & Doors.

**Features Overview**

- Unique exterior design.
- Series 9900 features 2 1/2" panels. Series 9901 features 4 1/2" wide french style door panels.
- Manufactured with extruded, high impact, UV-stabilized, multichambered, rigid polyvinyl chloride (PVC).
- Choose from White or Almond colors.
- Frames and panels are miter cut and fusion welded.
- 7/8" insulated glass with the Intercept® warm-edge spacer system.
- Frame depth is 5 1/2". Available with a 4 3/4" frame as Series 9500 and 9501.
- Nail-on fins are an integral part of the frame at the head and jambs with a 15/16" set back from the exterior edge of the frame.
- Interlocks and lock stiles are reinforced with aluminum extrusions for added structural strength and rigidity.
- Dual-point locking handle featuring a crescent pull is standard. Key lock and a variety of handle finishes are available.
- Adjustable tandem ball bearing rollers are used for ease of operation.
- Operating panel rolls on a stainless steel cap that is mounted on a heavy-duty aluminum track.
- Fin seal weatherstripping provides a barrier against air and water infiltration. Double weatherstripping at the sill ensures a smoother rolling action.
- Prestige Sliding Screen Door with heavy-duty extruded aluminum and steel rollers is standard.
- Many grid and glass options available.
- Available in standard or custom sizes.

**Standard Heights** include  
 67 = 78 1/2" • 68 = 79 1/2" • 80 = 95 1/2"  
 Callout Height = Net Height

**Configurations**




**2-Panel**  
XO / OX

X = Operable Panel  
O = Fixed Panel



**3-Panel**  
OXOL / OXOR  
XOO / OOX



**4-Panel**  
OXXO / XOOX

6<sup>8</sup> high doors are field reversible.

**Frame Types**

- » **Nail-on** Series 9900 / 9901  
 2-Panel XO / OX Net Frame Size:  
 Callout size minus 1/2" width and height.  
 3-Panel OXOL / OXOR Net Frame Size:  
 Callout size minus 1/8" width and 1/2" height.  
 3-Panel XOO / OOX Net Frame Size:  
 Callout size plus 1/8" width and minus 1/2" height.  
 4-Panel OXXO Net Frame Size:  
 Callout size minus 2 7/16" width and plus 1/2" height.  
 4-Panel XOOX Net Frame Size:  
 Callout size minus 1 15/16" width and plus 1/2" height.
- » **Block** Series 9950 / 9951
- » **Retrofit** Series 9990 / 9991
- » **Brick Mould** Series 9994 / 9995

**Thermal Ratings**

As tested with Climate Shield™ with Silvercoat<sup>3</sup> high performance glazing system featuring Low-E<sup>3</sup> glass.

|             | Low-E <sup>3</sup> | Low-E <sup>3</sup> + Argon* |
|-------------|--------------------|-----------------------------|
| 9900 / 9901 |                    |                             |
| SHGC        | .23 / .20          | .22 / .19                   |
| U-Factor    | .34 / .37          | .30 / .34                   |

Energy saving glass option includes Climate Shield™ with Silvercoat<sup>3</sup>. NFRC rated for thermal performance.

\*Both U-Factor and SHGC must be .30 or lower to qualify for the 2009/2010 Federal tax credit.



**Structural Ratings**

Meet and exceed AAMA specifications.

|         |       |
|---------|-------|
| 9900 xo | C 30  |
| 9901 xo | LC 25 |



*Ideal For Replacement & New Construction*  
**Premium Vinyl Doors • Series 9300 & 9301**  
**French Swing Doors**

**The Best Is Always Superior™**

*Product Information Sheet*

Series 9300 and 9301 Premium Vinyl French Swing Doors are manufactured in California by Superior Windows & Doors.

**Features Overview**

- Unique exterior design.
- Series 9300 features inswing operable panels and Series 9301 features outswing operable panels.
- Manufactured with extruded, high impact, UV-stabilized, multichambered, rigid polyvinyl chloride (PVC).
- Choose from White or Almond colors.
- Frames and panels are miter cut and fusion welded.
- 7/8" insulated glass with the Intercept® warm-edge spacer system.
- Frame depth is 5 11/16".
- Nail-on fins are an integral part of the frame at the head and jambs with a 1" set back from the exterior edge of the frame.
- Vertical frame and panel members are reinforced with aluminum extrusions for added structural strength and rigidity.
- Secure multipoint locking system with top, bottom, and center locking is standard.
- Adjustable door hinges are standard.
- Extruded aluminum threshold is standard in Gold Anodized and White, Almond, or Bronze painted finishes.
- Compression weatherstripping provides a barrier against air and water infiltration.
- Fixed or hinged (inswing) sidelites available. Hinged sidelites are not available with 80 high doors.
- Many grid and glass options available.
- Available in standard or custom sizes.


**Configurations**

Viewed From Exterior




**1-Panel**  
XL / XR


X = Operable Panel  
 O = Fixed Panel  
 F = Fixed Sidelite  
 H = Hinged Sidelite



**2-Panel**  
XXL / XXR  
XOL / XOR / OXL / OXR



**1-Panel with Sidelites**  
FXFL / FXFR  
HXHL / HXHR



**2-Panel with Sidelites**  
FXXFL / FXXFR  
HXXHL / HXXHR

**Standard Heights include**

67 = 78 1/2" • 68 = 79 1/2" • 80 = 95 1/2"  
 Callout Height = Net Height

**Frame Types**

- » **Nail-on** Series 9300 / 9301  
 1-Panel Net Frame Size:  
 Callout size plus 3/8" width and minus 1/2" height.  
 2-Panel Net Frame Size:  
 Callout size minus 5/8" width and 1/2" height.
- » **Retrofit** Series 9390 / 9391
- » **Brick Mould** Series 9394 / 9395

**Thermal Ratings**

As tested with Climate Shield™ with Silvercoat<sup>3</sup> high performance glazing system featuring Low-E<sup>3</sup> glass.

|         | Low-E <sup>3</sup> | Low-E <sup>3</sup> + Argon* |
|---------|--------------------|-----------------------------|
| SHGC    | .18                | .18                         |
| U-Value | .36                | .30                         |

Energy saving glass option includes Climate Shield™ with Silvercoat<sup>3</sup>. NFRC rated for thermal performance.

\*Both U-Factor and SHGC must be .30 or lower to qualify for the 2009/2010 Federal tax credit.

**Structural Ratings**

Meet and exceed AAMA specifications.

XXR LC 25



| Hardware       | Door Handle | Sidelite Latch | Door Hinge | Sidelite Hinge |
|----------------|-------------|----------------|------------|----------------|
| White          | ✓           | ✓              | ✓          | ✓              |
| Brite Brass    | ✓           |                | ✓          | ✓              |
| Antique Brass  | ✓           |                | ✓          | ✓              |
| Brite Chrome   | ✓           |                | ✓          | ✓              |
| Brushed Chrome | ✓           |                | ✓          | ✓              |
| Dark Bronze    | ✓           |                | ✓          | ✓              |
| Almond         | ✓           | ✓              | ✓          | ✓              |